

# WAGATE® GATE VALVE

## SVM-TG 160

|   |                 |
|---|-----------------|
| <b>Model Name</b>                                 | SVM-TG160       |
| <b>Nominal Diameter</b>                           | DN/OD 160       |
| <b>Pipe Type</b>                                  | SDR 17          |
| <b>Spindle Mtrl.</b>                              | Duplex SAF 2205 |
| <b>Spindle Nut Mtrl.</b>                          | CuSn12          |
| <b>Valve Body Mtrl.</b>                           | PE              |
| <b>Watertightness</b>                             | DIN 19569-4     |
| <b>Revs open [-]</b>                              | 41              |
| <b>Thread pitch [mm]</b>                          | 4               |
| <b>Torque [Nm]</b>                                | 11              |
| <b>Weight [kg]</b>                                | 14              |
| <b>Max. On-Seating pressure [mH<sub>2</sub>O]</b> | 60              |

## Product Variants

|                            |                  |
|----------------------------|------------------|
| <b>Art. No</b>             | <b>V70076160</b> |
| <b>Fasteners mtrl.</b>     | EN 1.4404        |
| <b>Gasket Mtrl.</b>        | EPDM             |
| <b>Knife Mtrl.</b>         | EN 1.4404        |
| <b>Reinforcement Mtrl.</b> | EN 1.4404        |

